

# **Stiro-settlometer**

## **Technical specifications**

### **General**

Motor casing: ABS with On-Off button and power jack  
Electric motor: 1 rpm  
Stirring rods: Aluminum  
Graduated cylinder: Acrylic 2 litres  
Scale #1: 0-1000 mL for SSVI or SVI  
Scale #2: 0-28 cm for ZSV  
Electrical supply (transformer 24V) : 100-240VAC, 50-60 Hz

For indoor usage only  
Installation category II  
Operating temperature: 0 to 35 °C  
pH : 6 to 9  
Air humidity : 80 % max  
Altitude : 2000 m max

### **Dimensions**

Diameter: 100 mm or 4 inches  
Cylinder height: 340 mm or 13,4 inches  
Motor + cylinder height: 420 mm or 16,5 inches

### **Weight**

Motor + cylinder: 818 g or 1,8 lb  
Cylinder alone: 0,54 kg or 1,2 lb

### **Shipping**

#### **Stiro-settlometer kit (SSVI and SVI)**

Box: 47 cm x 17 cm x 31 cm and 2,6 kg or 19 in x 7 in x 13 in and 5,8 lbs

#### **Stirro-settlometer (SSVI only)**

Box: 47 cm x 16 cm x 16 cm and 1,5 kg or 19 in x 6 in x 6 in and 3 lbs